


Single Row Tapered Roller Bearing

30300 Series-30314J2/Q



BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designação **30314J2/Q**

Dimensões principais (mm)

d1 70

D 150

B 38

Classificações básicas de carga (KN)

dyc (Cr) 220

stc (Cor) 260

Pu **31**

Avaliações de velocidade (rpm)

Classificações de 3400

velocidade

Limitando a velocidade 4500

Peso (Kg) 2.90

ISO335

Dimensões (ABMA) 2GB

Dimensões [mm]

d 70

d1 105

B 35

C **30**r1,2 (min) **3**

r3,4 (min) 2.5

uma 29

Dimensões de abutment e filete [mm]

da (max) 90

db (min) 82

Da (min) 130

Da (max) 138

Db (min) 140

Ca (min) 5

Cb (min) 8

ra (max) 2.5

rb (max) **2**

Valor

e 0.35

Y 1.7

Yo 0.9

GQZ high quality 30300 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com