


Single Row Tapered Roller Bearing

30300 Series-30332J2



BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designação	30332J2
Dimensões principais (mm)	
d1	160
D	340
B	75
Classificações básicas de carga (KN)	
dyc (Cr)	913
stc (Cor)	1180
Pu	114
Avaliações de velocidade (rpm)	
Classificações de velocidade	1500
Limitando a velocidade	2000
Peso (Kg)	29.0
ISO335	
Dimensões (ABMA)	2GB
Dimensões [mm]	
d	160
d1	233
B	68
C	58
r1,2 (min)	5
r3,4 (min)	4
uma	61
Dimensões de abutment e filete [mm]	
da (max)	201
db (min)	180
Da (min)	290
Da (max)	323
Db (min)	310
Ca (min)	9
Cb (min)	17
ra (max)	4
rb (max)	3
Valor	
e	0.35
Y	1.7
Yo	0.9

GQZ high quality 30300 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com