
Single Row Tapered Roller Bearing

31300 Series-31317J2





WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designação	**31317J2**
Dimensões principais (mm)	
d1	85
D	180
B	44.5
Classificações básicas de carga (KN)	
dyc (Cr)	242
stc (Cor)	285
Pu	33.5
Avaliações de velocidade (rpm)	
Classificações de velocidade	2600
Limitando a velocidade	3800
Peso (Kg)	4.60
ISO335	
Dimensões (ABMA)	7GB
Dimensões □mm□	
d	85
d1 □	**131**
B	41
C	28
r1,2 (min)	4
r3,4 (min)	**3**
uma	55
Dimensões de abutment e filete □mm□	
da (max)	103
db (min)	99
Da (min)	143
Da (max)	166
Db (min)	169
Ca (min)	6
Cb (min)	16.5
ra (max)	**3**
rb (max)	2.5
Valor	
e	0.83
Y	0.72
Yo	0.4

GQZ high quality 31300 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com