
Single Row Tapered Roller Bearing

31300 Series-31328XJ2





WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designação	**31328XJ2**
Dimensões principais (mm)	
d1	140
D	300
B	77
Classificações básicas de carga (KN)	
dyc (Cr)	693
stc (Cor)	900
Pu	88
Avaliações de velocidade (rpm)	
Classificações de velocidade	1500
Limitando a velocidade	2200
Peso (Kg)	24.5
ISO335	
Dimensões (ABMA)	7GB
Dimensões □mm□	
d	140
d1 □	219
B	70
C	47
r1,2 (min)	5
r3,4 (min)	4
uma	90
Dimensões de abutment e filete □mm□	
da (max)	169
db (min)	160
Da (min)	235
Da (max)	283
Db (min)	280
Ca (min)	9
Cb (min)	30
ra (max)	4
rb (max)	**3**
Valor	
e	0.83
Y	0.72
Yo	0.4

GQZ high quality 31300 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com