

Single Row Tapered Roller Bearing

32000 Series-32048X



BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designação	32048X
Dimensões principais (mm)	
d1	240
D	360
B	76
Classificações básicas de carga (KN)	
dyc (Cr)	935
stc (Cor)	1800
Pu	160
Avaliações de velocidade (rpm)	
Classificações de velocidade	1200
Limitando a velocidade	1600
Peso (Kg)	27.5
ISO335	
Dimensões (ABMA)	4FD
Dimensões [mm]	
d	240
d1	299
B	76
C	57
r1,2 (min)	4
r3,4 (min)	3
uma	78
Dimensões de abutment e filete [mm]	
da (max)	262
db (min)	256
Da (min)	318
Da (max)	345
Db (min)	346
Ca (min)	12
Cb (min)	19
ra (max)	3
rb (max)	2.5
Valor	
e	0.46
Y	1.3
Yo	0.7

GQZ high quality 32000 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com