

## Single Row Tapered Roller Bearing

32000 Series-32052X



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designação	<b>32052X</b>
Dimensões principais (mm)	
d1	260
D	400
B	87
Classificações básicas de carga (KN)	
dyc (Cr)	1170
stc (Cor)	2200
Pu	190
Avaliações de velocidade (rpm)	
Classificações de velocidade	1100
Limitando a velocidade	1400
Peso (Kg)	40.0
ISO335	
Dimensões (ABMA)	4FC
Dimensões [mm]	
d	260
d1	328
B	87
C	65
r1,2 (min)	<b>5</b>
r3,4 (min)	4
uma	84
Dimensões de abutment e filete [mm]	
da (max)	287
db (min)	282
Da (min)	352
Da (max)	383
Db (min)	383
Ca (min)	13
Cb (min)	22
ra (max)	4
rb (max)	<b>3</b>
Valor	
e	0.43
Y	1.4
Yo	0.8

## GQZ high quality 32000 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com