


Single Row Tapered Roller Bearing

32000 Series-32060X



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designação	32060X
Dimensões principais (mm)	
d1	300
D	460
B	100
Classificações básicas de carga (kN)	
dyc (Cr)	1540
stc (Cor)	3000
Pu	250
Avaliações de velocidade (rpm)	
Classificações de velocidade	900
Limitando a velocidade	1200
Peso (Kg)	58.0
ISO335	
Dimensões (ABMA)	4GD
Dimensões [mm]	
d	300
d1	377
B	100
C	74
r1,2 (min)	5
r3,4 (min)	4
uma	97
Dimensões de abutment e filete [mm]	
da (max)	330
db (min)	322
Da (min)	404
Da (max)	440
Db (min)	439
Ca (min)	15
Cb (min)	26
ra (max)	4
rb (max)	3
Valor	
e	0.43
Y	1.4
Yo	0.8

GQZ high quality 32000 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com