

Single Row Tapered Roller Bearing

33200 Series-33219



BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designação	33219
Dimensões principais (mm)	
d1	95
D	170
B	58
Classificações básicas de carga (KN)	
dyc (Cr)	374
stc (Cor)	560
Pu	62
Avaliações de velocidade (rpm)	
Classificações de velocidade	2600
Limitando a velocidade	3800
Peso (Kg)	5.50
ISO335	
Dimensões (ABMA)	3FE
Dimensões [mm]	
d	95
d1	132
B	58
C	44
r1,2 (min)	3
r3,4 (min)	2.5
uma	42
Dimensões de abutment e filete [mm]	
da (max)	107
db (min)	107
Da (min)	144
Da (max)	158
Db (min)	163
Ca (min)	9
Cb (min)	14
ra (max)	2.5
rb (max)	2
Valor	
e	0.40
Y	1.5
Yo	0.8

GQZ high quality 33200 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com