

## Single Row Angular Contact Ball Bearings

7000 Series angular contact ball bearings-7006DT,7006DF,7006DB,7006C 

## Bearing Numbers

Single row	<b>7006C</b>
DB	<b>7006DB</b>
DF	<b>7006DF</b>
DT	<b>7006DT</b>

## Dimensões principais (mm)

d	30
D	55
B	13
r (min)	1
r1(min)	0.6

## Basic load ratings(N)

Cr	15100
Cor	10300

## Classificações básicas de carga (kgf)

Cr	1540
Cor	1050

## Valor

fo	14.9
----	------

## Velocidade limite (rpm)

Graxa	19000
Óleo	26000



## Distance of action point(mm)



uma	12.2
-----	------

## Abutment and fillet dimensions

da (min)	36
Da (max)	49
ra (max)	1

## Peso

(kg)	0.134
------	-------

## Basic load ratings(duplex bearing) (N)

Cr	24600
Cor	20500

## Basic load ratings(duplex bearing) (kgf)

Cr	2510
Cor	2090

## Limiting Speed(duplex bearing) (rpm)

Graxa	15000
Óleo	22000

## Distance of action point (duplex bearing)(a0)

back-to-back arrangement	24.4
face-to-face arrangement	1.6

## Installation dimensions(duplex bearing)

db (min)	1-1 / 16
Db(max)	50
rb (max)	0.6

## GQZ bearing wholesale high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis.

**Model:7000 series**

**Bore (Inner) Diameter: 10 mm**□

**Outer Diameter: 26 mm**□

**Width (Thickness): 16mm;**

The 7000 series bearings contain models 7000CTA-2RZ/P5 single, 7001CTA-2RZ/P5 single, 7002CTA-2RZ/P5

single, 7003CTA-2RZ/P5 single, 7004CTA-2RZ/P5 single, 7005CTA-2RZ/P5 single, 7000CTA-2RZ/P4 single,

7001CTA-2RZ/P4 single, 7002CTA-2RZ/P4 single, 7003CTA-2RZ/P4 single, 7004CTA-2RZ/P4 single,

7005CTA-2RZ/P4 single. These models cover a wide range of specifications and configurations, including

single use and paired use, as well as different accuracy levels (P4 and P5) for a variety of application

scenarios. Models 7006CTA-2RZ/P4 paired and 7007CTA-2RZ/P4 paired are also available, providing

more options to meet different needs. These bearing types include angular contact ball bearings, which

are able to withstand radial and axial loads and can also operate at higher speeds, making them one of

the commonly used bearing types in mechanical systems.

