

## Single Row Angular Contact Ball Bearings

7000 Series angular contact ball bearings-7010DT,7010DF,7010DB,7010A 

## Bearing Numbers

Single row	<b>7010A</b>
DB	<b>7010DB</b>
DF	<b>7010DF</b>
DT	<b>7010DT</b>

## Dimensões principais (mm)

d	50
D	80
B	16
r (min)	<b>1</b>
r1(min)	0.6

## Basic load ratings(N)

Cr	24500
Cor	21100

## Classificações básicas de carga (kgf)

Cr	2500
Cor	2150

## Valor

fo	16
----	----

## Velocidade limite (rpm)

Graxa	8500
Óleo	12000



## Distance of action point(mm)



uma	26.8
-----	------

## Abutment and fillet dimensions

da (min)	56
Da (max)	74
ra (max)	<b>1</b>

## Peso

(kg)	0.263
------	-------

## Basic load ratings(duplex bearing) (N)

Cr	40000
Cor	42000

## Basic load ratings(duplex bearing) (kgf)

Cr	4050
Cor	4300

## Limiting Speed(duplex bearing) (rpm)

Graxa	7100
Óleo	9500

## Distance of action point (duplex bearing)(a0)

back-to-back arrangement	53.5
face-to-face arrangement	21.5

## Installation dimensions(duplex bearing)

db (min)	55
Db(max)	75
rb (max)	0.6

## GQZ bearing wholesale high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis.

**Model:7000 series**

**Bore (Inner) Diameter: 10 mm**□

**Outer Diameter: 26 mm**□

**Width (Thickness): 16mm;**

The 7000 series bearings contain models 7000CTA-2RZ/P5 single, 7001CTA-2RZ/P5 single, 7002CTA-2RZ/P5

single, 7003CTA-2RZ/P5 single, 7004CTA-2RZ/P5 single, 7005CTA-2RZ/P5 single, 7000CTA-2RZ/P4 single,

7001CTA-2RZ/P4 single, 7002CTA-2RZ/P4 single, 7003CTA-2RZ/P4 single, 7004CTA-2RZ/P4 single,

7005CTA-2RZ/P4 single. These models cover a wide range of specifications and configurations, including

single use and paired use, as well as different accuracy levels (P4 and P5) for a variety of application

scenarios. Models 7006CTA-2RZ/P4 paired and 7007CTA-2RZ/P4 paired are also available, providing

more options to meet different needs. These bearing types include angular contact ball bearings, which

are able to withstand radial and axial loads and can also operate at higher speeds, making them one of

the commonly used bearing types in mechanical systems.

