
## Single Row Angular Contact Ball Bearings

7000 Series-7003DT,7003DF,7003DB,7003C







## WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers	
Single row	7003C
DB	7003DB
DF	7003DF
DT	7003DT
Dimensões principais (mm)	
d	17
D	35
В	10
r (min)	0.3
r1(min)	0.15
Basic load ratings(N)	
Cr	6600
Cor	3800
Classificações básicas d	
Cr	675
Cor	390
Valor	
fo	14.5
Velocidade limite (rpm)	
Graxa	32000
Óleo	43000
Distance of action point	
uma	8.5
Abutment and fillet dim	
da (min)	19.5
Da (max)	32.5
ra (max)	0.3
Peso	0.044
(kg)	0.044
Basic load ratings(duple	_
Cr	10700
Cor	7600
Basic load ratings(duple	
Cr	1100
Cor	775
Limiting Speed(duplex bearing) (rpm)	
Graxa	26000
Óleo	34000
Distance of action point	
back-to-back	17
arrangement	2
face-to-face	3
arrangement Installation dimensions(duplex bearing)	
db (min)	1-1 / 16
Db(max)	33.8
rb (max)	0.15

## **GQZ** high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com,shary@gqbearing.com