
Single Row Angular Contact Ball Bearings

7000 Series-7008DT,7008DF,7008DB,7008C







WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers	
Single row	7008C
DB	7008DB
DF	7008DF
DT	7008DT
Dimensões principais (mm)	
d	40
D	68
В	15
r (min)	1
r1(min)	0.6
Basic load ratings(N)	
Cr	20600
Cor	15900
Classificações básicas de carga (kgf)	
Cr	2100
Cor	1620
Valor	
fo	15.4
Velocidade limite (rpm)	
Graxa	15000
Óleo	20000
Distance of action point	(mm)
uma .	14.7
Abutment and fillet dimensions	
da (min)	46
Da (max)	62
ra (max)	1
Peso	
(kg)	0.212
Basic load ratings(duple	
Cr	33500
Cor	32000
Basic load ratings(duple	
Cr	3400
Cor	3250
Limiting Speed(duplex I	
Graxa	12000
Óleo	17000
Distance of action point	
back-to-back	29.5
arrangement	23.3
face-to-face	0.5
arrangement	0.5
Installation dimensions(duplex bearing)	
db (min)	1-1 / 16
Db(max)	63
rb (max)	0.6
ib (iliax)	0.0

GQZ high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com,shary@gqbearing.com