

Single Row Angular Contact Ball Bearings

7000 Series-7012DT,7012DF,7012DB,7012C



BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers

Single row	7012C
DB	7012DB
DF	7012DF
DT	7012DT

Dimensões principais (mm)

d	60
D	95
B	18
r (min)	1.1
r1(min)	0.6

Basic load ratings(N)

Cr	35000
Cor	30500

Classificações básicas de carga (kgf)

Cr	3600
Cor	3150

Valor

fo	15.6
----	------

Velocidade limite (rpm)

Graxa	10000
Óleo	14000

Distance of action point(mm)

uma	19.4
-----	------

Abutment and fillet dimensions

da (min)	67
Da (max)	88
ra (max)	1

Peso

(kg)	0.46
------	------

Basic load ratings(duplex bearing) (N)

Cr	57000
Cor	61500

Basic load ratings(duplex bearing) (kgf)

Cr	5800
Cor	6250

Limiting Speed(duplex bearing) (rpm)

Graxa	8500
Óleo	12000

Distance of action point (duplex bearing)(a0)

back-to-back arrangement	38.8
--------------------------	------

face-to-face arrangement	2.8
--------------------------	-----

Installation dimensions(duplex bearing)

db (min)	1-1 / 16
Db(max)	90
rb (max)	0.6

GQZ high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com