

Single Row Angular Contact Ball Bearings

7000 Series-7013DT,7013DF,7013DB,7013C



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers

Single row	7013C
DB	7013DB
DF	7013DF
DT	7013DT

Dimensões principais (mm)

d	65
D	100
B	18
r (min)	1.1
r1(min)	0.6

Basic load ratings(N)

Cr	37000
Cor	34500

Classificações básicas de carga (kgf)

Cr	3800
Cor	3500

Valor

fo	15.9
----	------

Velocidade limite (rpm)

Graxa	10000
Óleo	13000

Distance of action point(mm)

uma	20
-----	----

Abutment and fillet dimensions

da (min)	72
Da (max)	93
ra (max)	1

Peso

(kg)	0.493
------	-------

Basic load ratings(duplex bearing) (N)

Cr	60500
Cor	68500

Basic load ratings(duplex bearing) (kgf)

Cr	6150
Cor	7000

Limiting Speed(duplex bearing) (rpm)

Graxa	8000
Óleo	11000

Distance of action point (duplex bearing)(a0)

back-to-back arrangement	40.1
--------------------------	------

face-to-face arrangement	4.1
--------------------------	-----

Installation dimensions(duplex bearing)

db (min)	1-1 / 16
Db(max)	95
rb (max)	0.6

GQZ high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com