


Single Row Angular Contact Ball Bearings

7000 Series-7018DT,7018DF,7018DB,7018C



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers

Single row	7018C
DB	7018DB
DF	7018DF
DT	7018DT

Dimensões principais (mm)

d	90
D	140
B	24
r (min)	1.5
r1(min)	1

Basic load ratings(N)

Cr	71500
Cor	69000

Classificações básicas de carga (kgf)

Cr	7300
Cor	7050

Valor

fo	15.7
----	------

Velocidade limite (rpm)

Graxa	7100
Óleo	9500

Distance of action point(mm)

uma	27.4
-----	------

Abutment and fillet dimensions

da (min)	99
Da (max)	131
ra (max)	1.5

Peso

(kg)	1.34
------	------

Basic load ratings(duplex bearing) (N)

Cr	116000
Cor	138000

Basic load ratings(duplex bearing) (kgf)

Cr	11900
Cor	14100

Limiting Speed(duplex bearing) (rpm)

Graxa	5600
Óleo	8000

Distance of action point (duplex bearing)(a0)

back-to-back arrangement	54.8
--------------------------	------

face-to-face arrangement	6.8
--------------------------	-----

Installation dimensions(duplex bearing)

db (min)	1-1 / 16
Db(max)	134
rb (max)	1

GQZ high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com