
Single Row Angular Contact Ball Bearings

7000 Series-7019DT,7019DF,7019DB,7019C







WUXI GUANGQIANG BEARING TRADE CO.,LTD

Posring Numbers	
Bearing Numbers	70106
Single row	7019C
DB	7019DB
DF	7019DF
DT	7019DT
Dimensões principais (mm)	
d	95
D	145
В,	24
r (min)	1.5
r1(min)	1
Basic load ratings(N)	
Cr	73500
Cor	73000
Classificações básicas d	
Cr	7500
Cor	7450
Valor	
fo	15.9
Velocidade limite (rpm)	
Graxa	6700
Óleo	9000
Distance of action point	(mm)
uma	28.1
Abutment and fillet dimensions	
da (min)	104
Da (max)	136
ra (max)	1.5
Peso	
(kg)	1.42
Basic load ratings(duple	ex bearing) (N)
Cr	119000
Cor	146000
Basic load ratings(duple	ex bearing) (kgf)
Cr	12200
Cor	14900
Limiting Speed(duplex b	
Graxa	5300
Óleo	7500
Distance of action point	
back-to-back	561
arrangement	301
face-to-face	8.1
arrangement	0.1
Installation dimensions(duplex bearing)	
db (min)	1-1 / 16
Db(max)	139
rb (max)	1
TO (ITION)	-

GQZ high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com,shary@gqbearing.com