
## Single Row Angular Contact Ball Bearings

7000 Series-7040DT,7040DF,7040DB,7040A







## WUXI GUANGQIANG BEARING TRADE CO.,LTD

Dooring Numbers	
Bearing Numbers	70404
Single row	7040A
DB	7040DB
DF	7040DF
DT	7040DT
Dimensões principais (mm)	
d	200
D	310
В	51
r (min)	2.1
r1(min)	1.1
Basic load ratings(N)	
Cr	240000
Cor	310000
Classificações básicas d	
Cr	24500
Cor	31500
Valor	
fo	16.2
Velocidade limite (rpm)	
Graxa	1700
Óleo	2200
Distance of action point	(mm)
uma	99.1
Abutment and fillet dimensions	
da (min)	212
Da (max)	298
ra (max)	2
Peso	
(kg)	13.7
Basic load ratings(duple	
Cr	390000
Cor	620000
Basic load ratings(duple	
Cr	40000
Cor	63500
Limiting Speed(duplex b	
Graxa	1300
Óleo	1800
Distance of action point	
back-to-back	198.2
arrangement	130.2
face-to-face	96.2
arrangement	30.2
Installation dimensions(duplex bearing)	
db (min)	1-1 / 16
Db(max)	303
rb (max)	1
ιυ (ιιιαλ)	1

## **GQZ** high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com,shary@gqbearing.com