

Single Row Angular Contact Ball Bearings

7000 Series angular contact ball bearings-7026DT,7026DF,7026DB,7026A 

Bearing Numbers

Single row	7026A
DB	7026DB
DF	7026DF
DT	7026DT

Dimensões principais (mm)

d	130
D	200
B	33
r (min)	2
r1(min)	1

Basic load ratings(N)

Cr	117000
Cor	125000

Classificações básicas de carga (kgf)

Cr	12000
Cor	12800

Valor

fo	16.2
----	------

Velocidade limite (rpm)

Graxa	3400
Óleo	4500



Distance of action point(mm)



uma	64.1
-----	------

Abutment and fillet dimensions

da (min)	140
Da (max)	190
ra (max)	2

Peso

(kg)	3.68
------	------

Basic load ratings(duplex bearing) (N)

Cr	191000
Cor	251000

Basic load ratings(duplex bearing) (kgf)

Cr	19400
Cor	25600

Limiting Speed(duplex bearing) (rpm)

Graxa	2600
Óleo	3600

Distance of action point (duplex bearing)(a0)

back-to-back arrangement	128.3
face-to-face arrangement	62.3

Installation dimensions(duplex bearing)

db (min)	1-1 / 16
Db(max)	194
rb (max)	1

GQZ bearing wholesale high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis.

Model:7000 series

Bore (Inner) Diameter: 10 mm

Outer Diameter: 26 mm

Width (Thickness): 16mm;

The 7000 series bearings contain models 7000CTA-2RZ/P5 single, 7001CTA-2RZ/P5 single, 7002CTA-2RZ/P5

single, 7003CTA-2RZ/P5 single, 7004CTA-2RZ/P5 single, 7005CTA-2RZ/P5 single, 7000CTA-2RZ/P4 single,

7001CTA-2RZ/P4 single, 7002CTA-2RZ/P4 single, 7003CTA-2RZ/P4 single, 7004CTA-2RZ/P4 single,

7005CTA-2RZ/P4 single. These models cover a wide range of specifications and configurations, including

single use and paired use, as well as different accuracy levels (P4 and P5) for a variety of application

scenarios. Models 7006CTA-2RZ/P4 paired and 7007CTA-2RZ/P4 paired are also available, providing

more options to meet different needs. These bearing types include angular contact ball bearings, which

are able to withstand radial and axial loads and can also operate at higher speeds, making them one of

the commonly used bearing types in mechanical systems.

