
Single Row Angular Contact Ball Bearings

7200 Series-7203DT,7203DF,7203DB,7203A





BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers		
Single row	7203A	
DB	7203DB	
DF	7203DF	
DT	7203DT	
Dimensões principais (mm)		
d	17	
D	40	
В	12	
r (min)	0.6	
r1(min)	0.3	
Basic load ratings(N)		
Cr	10800	
Cor	6000	
Classificações básicas d	e carga (kgf)	
Cr	1100	
Cor	610	
Valor		
fo	13.8	
Velocidade limite (rpm)		
Graxa	20000	
Óleo	28000	
Distance of action point		
uma	14.2	
Abutment and fillet dime	ensions	
da (min)	22	
Da (max)	35	
ra (max)	0.6	
Peso		
(kg)	0.067	
Basic load ratings(duple		
Cr	17600	
Cor	12000	
Basic load ratings(duple		
Cr	1790	
Cor	1220	
Limiting Speed(duplex b		
Graxa	16000	
Óleo	22000	
Distance of action point		
back-to-back	28.5	
	20.5	
arrangement face-to-face	4.5	
	4.5	
arrangement Installation dimensions(duplex bearing)		
	19.5	
db (min) Db(max)		
Db(max)	37.5	
rb (max)	0.3	

GQZ high quality 7200 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqb earing.com-http://www.bearing-asia.com