
Single Row Angular Contact Ball Bearings

7200 Series-7218DT,7218DF,7218DB,7218A







WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers	
Single row	7218A
DB	7218DB
DF	7218DF
DT	7218DT
Dimensões principais (mm)	
d	90
D	160
В	30
r (min)	2
r1(min)	1
Basic load ratings(N)	
Cr	118000
Cor	103000
Classificações básicas de carga (kgf)	
Cr	12000
Cor	10500
Valor	
fo	15.1
Velocidade limite (rpm)	
Graxa	4500
Óleo	6000
Distance of action point	(mm)
uma	51.1
Abutment and fillet dimensions	
da (min)	100
Da (max)	150
ra (max)	2
Peso	
(kg)	2.25
Basic load ratings(duplex bearing) (N)	
Cr	191000
Cor	206000
Basic load ratings(duplex bearing) (kgf)	
Cr	19500
Cor	21000
Limiting Speed(duplex bearing) (rpm)	
Graxa	3600
Óleo	5000
Distance of action point	(duplex bearing)(a0)
back-to-back	102.2
arrangement	
face-to-face	42.2
arrangement	
Installation dimensions(duplex bearing)	
db (min)	96
Db(max)	154
rb (max)	1
,	

GQZ high quality 7200 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqb earing.com-http://www.bearing-asia.com