

## Single Row Angular Contact Ball Bearings

7300 Series angular contact ball bearings-7308DT,7308DF,7308DB,7308A 

## Bearing Numbers

Single row	<b>7308A</b>
DB	<b>7308DB</b>
DF	<b>7308DF</b>
DT	<b>7308DT</b>

## Dimensões principais (mm)

d	40
D	90
B	23
r (min)	1.5
r1(min)	1

## Basic load ratings(N)

Cr	49000
Cor	33000

## Classificações básicas de carga (kgf)

Cr	5000
Cor	3350

## Valor

fo	14
----	----

## Velocidade limite (rpm)

Graxa	7100
Óleo	9000



## Distance of action point(mm)



uma	30.3
-----	------

## Abutment and fillet dimensions

da (min)	49
Da (max)	81
ra (max)	1.5

## Peso

(kg)	0.633
------	-------

## Basic load ratings(duplex bearing) (N)

Cr	79500
Cor	66000

## Basic load ratings(duplex bearing) (kgf)

Cr	8100
Cor	6700

## Limiting Speed(duplex bearing) (rpm)

Graxa	5600
Óleo	7500

## Distance of action point (duplex bearing)(a0)

back-to-back arrangement	60.5
face-to-face arrangement	14.5

## Installation dimensions(duplex bearing)

db (min)	46
Db(max)	84
rb (max)	1

# GQZ bearings wholesale high quality 7300 Series Single Row Angular Contact Ball Bearings

The dimensional parameters of 7300 series bearings include inner diameter of 10mm, outer diameter of 35mm and thickness of 11mm.

The 7300 series bearings belong to angular contact ball bearings, the specific models and sizes may be different, but the basic size parameters remain the same. For example, NSK 7300 bearings, 7300AC/DF angular contact ball bearings, 7300AC/DT angular contact ball bearings, NSK 7300BDB bearings, NACHI 7300 bearings, and NSK 7300BDT bearings, etc. Despite the differences in models and characteristics, their inner diameters, outer diameters, and thicknesses remain the same, at 10mm, 35mm, and 11mm respectively. These bearings are typically used in applications requiring radial and axial loads with high rotational accuracy and flexibility. In addition, some specific models of the 7300 series bearings have special lubrication properties and seal designs to meet different operating conditions and performance requirements.

## 7300 Angular Contact Ball Bearing Characteristics

**The characteristics of 7300 angular contact ball bearings mainly include high load carrying capacity, high rotational speed, good axial and radial load carrying capacity, as well as being suitable for occasions where high precision is required.**

**1 High load carrying capacity:** 7300 angular contact ball bearings are able to withstand both radial and axial loads, which makes it widely used in the field of industrial machinery. The bearings have a large load carrying capacity and can withstand a large number of radial and axial forces, thus dispersing the load, reducing the stress at a single contact point and prolonging the service life of the bearings.

**2 High speed:** Due to the design of 7300 angular contact ball bearings, the contact angle between the inner ring and outer ring is designed to be 15° or 25°, which reduces the frictional resistance and lowers the temperature rise, thus increasing the speed of the bearings. This makes it perform well in conditions that require high speed operation, such as machine tool spindles, high-speed motors and other high-precision, high speed mechanical equipment in a wide range of applications.

**3 Good axial and radial load carrying capacity:** 7300 angular contact ball bearings are designed to allow it to carry axial and radial loads. Although single row angular contact ball bearings can only withstand axial load in one direction, but in the radial load will cause additional axial force, so generally used in pairs to ensure stability and load carrying capacity.

**4 Suitable for occasions requiring high precision:** 7300 angular contact ball bearings have high precision and repeat positioning accuracy, and are suitable for mechanical equipment requiring high precision. Its manufacturing precision is very high, can use high-strength steel or ceramic material as rolling body, inner and outer ring using high-strength steel, reduce friction and wear, the internal filling of the right amount of grease, to further reduce the friction loss, so as to meet the requirements of high-precision machinery and equipment operation.



Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-  
Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com