

Single Row Angular Contact Ball Bearings

7900 Series-7906DT,7906DF,7906DB,7906C



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers

Single row	7906C
DB	7906DB
DF	7906DF
DT	7906DT

Dimensões principais (mm)

d	30
D	47
B	9
r (min)	0.3
r1(min)	0.15

Basic load ratings(N)

Cr	8300
Cor	6250

Classificações básicas de carga (kgf)

Cr	845
Cor	640

Valor

fo	15.9
----	------

Velocidade limite (rpm)

Graxa	22000
Óleo	28000

Distance of action point(mm)

uma	9.7
-----	-----

Abutment and fillet dimensions

da (min)	32.5
Da (max)	44.5
ra (max)	0.3

Peso

(kg)	0.049
------	-------

Basic load ratings(duplex bearing) (N)

Cr	13500
Cor	12500

Basic load ratings(duplex bearing) (kgf)

Cr	1380
Cor	1280

Limiting Speed(duplex bearing) (rpm)

Graxa	17000
Óleo	24000

Distance of action point (duplex bearing)(a0)

back-to-back arrangement	19.3
--------------------------	------

face-to-face arrangement	1.3
--------------------------	-----

Installation dimensions(duplex bearing)

db (min)	1-1 / 16
Db(max)	45.8
rb (max)	0.15

GQZ high quality 7900 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com