


Four Point Angular Contact Ball Bearing

5200 Series-5215



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designação	5215
Dimensões principais (mm)	
d	75
D	130
B	41.3
r (min)	1.5
Classificações básicas de carga (kN)	
Cr	93500
Cor	83000
Classificações básicas de carga (kgf)	
Cr	9550
Cor	8500
Velocidade limite (rpm)	
Graxa	3200
Óleo	4300
Distância do ponto de ação	
a0 (mm)	66.1
Dimensões de instalação (mm)	
da (min)	84
Da (max)	121
ra (max)	1.5
Peso	
(kg)	1.9

GQZ high quality 5200 Series Four Point Angular Contact Ball Bearing

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com