
Single Row Angular Contact Ball Bearings

7000 Series-7004DT,7004DF,7004DB,7004A





BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers	
Single row	7004A
DB	
DB DF	7004DB 7004DF
	7004DF 7004DT
DT Dimensãos principais (r	
Dimensões principais (r	
d	20
D	42
B	12
r (min)	0.6
r1(min)	0.3
Basic load ratings(N)	
Cr	10800
Cor	6600
Classificações básicas d	
Cr	1110
Cor	670
Valor	
fo	14.5
Velocidade limite (rpm)	
Graxa	18000
Óleo	24000
Distance of action point	:(mm)
uma	14.9
Abutment and fillet dim	ensions
da (min)	25
Da (max)	37
ra (max)	0.6
Peso	
(kg)	0.068
Basic load ratings(duple	ex bearing) (N)
Cr	17600
Cor	13200
Basic load ratings(duple	ex bearing) (kgf)
Cr	1800
Cor	1340
Limiting Speed(duplex b	
Graxa	15000
Óleo	20000
Distance of action point	
back-to-back	29.9
arrangement	23.3
face-to-face	5.9
arrangement	
Installation dimensions(duplex bearing)
db (min)	22.5
Db(max)	39.5
rb (max)	0.3
	0.5

GQZ high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqb earing.com-http://www.bearing-asia.com