


Single Row Angular Contact Ball Bearings

7200 Series-7203DT,7203DF,7203DB,7203A



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers

Single row **7203A**DB **7203DB**DF **7203DF**DT **7203DT**

Dimensões principais (mm)

d 17

D 40

B 12

r (min) 0.6

r1(min) 0.3

Basic load ratings(N)

Cr 10800

Cor 6000

Classificações básicas de carga (kgf)

Cr 1100

Cor 610

Valor

fo 13.8

Velocidade limite (rpm)

Graxa 20000

Óleo 28000

Distance of action point(mm)

uma 14.2

Abutment and fillet dimensions

da (min) 22

Da (max) 35

ra (max) 0.6

Peso

(kg) 0.067

Basic load ratings(duplex bearing) (N)

Cr 17600

Cor 12000

Basic load ratings(duplex bearing) (kgf)

Cr 1790

Cor 1220

Limiting Speed(duplex bearing) (rpm)

Graxa 16000

Óleo 22000

Distance of action point (duplex bearing)(a0)

back-to-back 28.5

arrangement

face-to-face 4.5

arrangement

Installation dimensions(duplex bearing)

db (min) 19.5

Db(max) 37.5

rb (max) 0.3

GQZ high quality 7200 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com