
Single Row Angular Contact Ball Bearings

7200 Series-7206DT,7206DF,7206DB,7206A







WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers	
Single row	7206A
DB	7206DB
DF	7206DF
DT	7206DT
Dimensões principais (mm)	
d	30
D	62
В	16
r (min)	1
r1(min)	0.6
Basic load ratings(N)	
Cr	22500
Cor	14800
Classificações básicas de carga (kgf)	
Cr	2300
Cor	1510
Valor	
fo	14.4
Velocidade limite (rpm)	
Graxa	12000
Óleo	17000
Distance of action point	(mm)
uma .	21.3
Abutment and fillet dimensions	
da (min)	36
Da (max)	56
ra (max)	1
Peso	
(kg)	0.197
Basic load ratings(duplex bearing) (N)	
Cr	36500
Cor	29500
Basic load ratings(duple	
Cr	3750
Cor	3000
Limiting Speed(duplex I	
Graxa	10000
Óleo	13000
Distance of action point	
back-to-back	42.6
arrangement	72.0
face-to-face	10.6
arrangement	10.0
Installation dimensions(duplex bearing)	
db (min)	35
Db(max)	57
rb (max)	0.6
ιυ (ιιιαλ)	0.0

GQZ high quality 7200 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqb earing.com-http://www.bearing-asia.com