


Single Row Angular Contact Ball Bearings

7200 Series-7206DT,7206DF,7206DB,7206B



BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers

Single row **7206B**DB **7206DB**DF **7206DF**DT **7206DT**

Dimensões principais (mm)

d 30

D 62

B 16

r (min) 1

r1(min) 0.6

Basic load ratings(N)

Cr 20500

Cor 13500

Classificações básicas de carga (kgf)

Cr 2090

Cor 1380

Valor

fo 14.9

Velocidade limite (rpm)

Graxa 8500

Óleo 12000

Distance of action point(mm)

uma 27.3

Abutment and fillet dimensions

da (min) 36

Da (max) 56

ra (max) 1

Peso

(kg) 0.202

Basic load ratings(duplex bearing) (N)

Cr 33500

Cor 27000

Basic load ratings(duplex bearing) (kgf)

Cr 3400

Cor 2760

Limiting Speed(duplex bearing) (rpm)

Graxa 7100

Óleo 9500

Distance of action point (duplex bearing)(a0)

back-to-back 54.6

arrangement

face-to-face 22.6

arrangement

Installation dimensions(duplex bearing)

db (min) 35

Db(max) 57

rb (max) 0.6

GQZ high quality 7200 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com