

Single Row Tapered Roller Bearing

32200 Series-32218J2/Q



BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designação **32218J2/Q**

Dimensões principais (mm)

d1 90

D 160

B 42.5

Classificações básicas de carga (KN)

dyc (Cr) 251

stc (Cor) 340

Pu 38

Avaliações de velocidade (rpm)

Classificações de 3000

velocidade

Limitando a velocidade 4000

Peso (Kg) 3.35

ISO335

Dimensões (ABMA) 3FC

Dimensões [mm]

d 90

d1 121

B 40

C 34

r1,2 (min) 2.5

r3,4 (min) **2**

uma 36

Dimensões de abutment e filete [mm]

da (max) 102

db (min) 101

Da (min) 138

Da (max) 150

Db (min) 152

Ca (min) 5

Cb (min) 8.5

ra (max) **2**rb (max) **2**

Valor

e 0.43

Y 1.4

Yo 0.8

GQZ high quality 32200 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com