

UK Series insert bearings

Insert Bearings

UK Series insert bearings



Model	Dimensions (mm)											capacity (kN)			Mass
	d ₂	d	D	L	B	C	d ₁	D ₁	W	Y	E	C	C ₀	Pu	kg
UK 205 2S	20	25	52	—	15	15	33.6	44	—	—	4.3	14	7.8	0.232	0.14
UK 205 2S+H 205	20	25	52	26	15	15	33.6	44	38	8	4.3	14	7.8	0.232	0.14
UK 206 2S	25	30	62	—	16	16	39.7	51.6	—	—	5.1	19.5	11.3	0.335	0.18
UK 206 2S+H 206	25	30	62	27	16	16	39.7	51.6	45	8	5.1	19.5	11.3	0.335	0.18
UK 207 2S	30	35	72	—	17	17	46.1	60.5	—	—	5.6	25.5	15.3	0.445	0.28
UK 207 2S+H 207	30	35	72	29	17	17	46.1	60.5	52	9	5.6	25.5	15.3	0.445	0.28
UK 208 2S	35	40	80	—	18	18	52	67.3	—	—	6.1	32.5	19.8	0.56	0.36
UK 208 2S+H 208	35	40	80	31	18	18	52	67.3	58	10	6.1	32.5	19.8	0.56	0.36
UK 209 2S	40	45	85	—	19	19	56.6	72.6	—	—	6.1	32.5	20.4	0.64	0.39
UK 209 2S+H 209	40	45	85	33	19	19	56.6	72.6	65	11	6.1	32.5	20.4	0.64	0.39
UK 210 2S	45	50	90	—	20	20	62.5	78.2	—	—	6.4	35	23.2	0.695	0.44
UK 210 2S+H 210	45	50	90	55	20	20	62.5	78.2	70	12	6.4	35	23.2	0.695	0.44
UK 211 2S	50	55	100	—	21	21	69.1	85.9	—	—	7	43.5	29	0.865	0.59
UK 211 2S+H 211	50	55	100	59	21	21	69.1	85.9	75	12	7	43.5	29	0.865	0.59
UK 212 2S	55	60	110	—	22	22	75.5	95	—	—	7.7	52	36	1.06	0.75
UK 212 2S+H 212	55	60	110	62	22	22	75.5	95	80	13	7.7	52	36	1.06	0.75